

WarmRain Specification for model:
B-6036



Warm Rain models B-6036 shower base fixtures are constructed of reinforced polyester resin covered with a high gloss gel-coat of 18 - 20 mil. thickness. The reinforced fiberglass has a minimum content of 18 % fiberglass.

The bottom base of the unit is constructed of 1/2" end-grained balsa wood sandwiched between 2 layers of reinforced fiberglass at a content of no less than 18%. The base is an integral part of the unit.

The inside bottom floor will be textured. The texture bottom floor meets and exceeds ASTM Safety Specification F-462.

The unit will measure 60" x 36" x 7" and has a 3" front outside threshold with an inside dam that is 1.5" inside dam. The door opening is 56 3/4".


The B-6036 is available with the Above Floor rough-in. Please see Measurement Sheet B-6036 AFR for more specific measurements.

The front apron of all units will have wood support along the entire length to help prevent the corners from chipping or bowing in or out.


These Warm Rain showers arrive on site fully tested, inspected, and certified to meet or exceed the precise standards established by FHA/HUD, materials bulletin 73, American National Standards Z-124.1 and Z-124.2, ASTM/E-84 and is certified by the National Association of Home Builders NAHB.



WarmRain Specification for model:
B-6036



B-6036



4-9-19

