## Warm Rain Specification for models:

## WR 672SPD and WR 673SPD BIG OLE Whirlpools

(Extra Long, Extra Wide and Extra Deep Tub/shower Whirlpool)



Warm Rain BIG OLE models WR 672SPD (right hand plbg.) and WR 673SPD (left hand plbg.) tub/shower whirlpools are constructed of reinforced polyester resin covered with a high gloss gel-coat of 18 - 20 mil. thickness. The reinforced fiberglass has a minimum content of 18 % fiberglass.

The bottom base of the unit is constructed of 1/2" end-grained balsa wood sandwiched between 2 layers of reinforced fiberglass. The base is an integral part of the unit.

The inside bottom floor will be textured. The texture bottom floor meets and exceeds ASTM Safety Specification F-462.

The unit will measure 72" x 35.75" x 76.5" and has a 20" apron height. The inside dam will measure 17.25" and the overflow will be 15.5" above the floor.

The inside sump area will measure  $63'' \times 26''$  at the top of the well and  $55'' \times 23.5''$  at the bottom of the well.

The front apron of all units will have wood support along the entire length to help prevent the corners from chipping or bowing in or out.

The BIG OLE WR 672SPD and WR 673SPD will have wood support for a shower door and a curtain bracket. The whirlpool system includes the following:

- 1 HP NuWhirl Hercules II self-draining pump with a plug and located opposite the drain
  - 120 Volts
  - 7 AMP
  - o 60Hz
- 6 color coded (white, Biscuit/Linen, Almond/Bone) jets strategically located throughout the tub
- 1 Pneumatic On/Off Switch
- 1 Silent air control
- Trim
  - Color coded in white, almond/bone, biscuit/linen
  - o Chrome trim in all other colors

## Whirlpool options include:

- HydroQuip HeatMaster T-Heater (separate dedicated electrical circuit needed)
  - 120 Volts
  - o 12.0 AMP
  - o 60 Hz

Warm Rain Corporation, P.O. Box 600, Hancock, MI 49930

Voice: 906-482-3750 Fax: 906-482-2585 email: <u>tedk@warmrain.com</u> website: <u>www.warmrain.com</u>

Page 1 of 2




## WR 672SPD and WR 673SPD BIG OLE Whirlpools


(Extra Long, Extra Wide and Extra Deep Tub/shower Whirlpool)


- Vari-flow pump allows the end user infinite speed control
- 1 Optional pump position
- whirlpool/air tub combination system
- Chrome Trim
- Brushed Nickel Trim

These Warm Rain tub/shower whirlpools arrive on site fully tested, inspected, and certified to meet or exceed the precise standards established by FHA/HUD, materials bulletin 73, American National Standards Z-124.1 and Z-124.2, ASTM/E-84 and is certified by the Home Innovation Research Labs, formerly known as the National Association of Home Builders NAHB.



WR 672/3 D (Revised)





6-5-1



Warm Rain Corporation, P.O. Box 600, Hancock, MI 49930

Voice: 906-482-3750 Fax: 906-482-2585 email: <u>tedk@warmrain.com</u> website: <u>www.warmrain.com</u>

Page 2 of 2